


OVERVIEW



1. Power connector	3. HDMI 1.4
2. Audio-out (3.5mm)	4. DisplayPort 1.4

PERFORMANCE

Panel

- Panel**
3-side NearEdgeless, VA
- Backlight**
WLED
- Display Size**
27 inches
- Max View Area**
WxH: 597.89 x 336.31 mm
- Resolution**
2560 x 1440
- Aspect Ratio**
16:9
- Pixel Pitch**
0.233 x 0.233 mm
- Dot / Pixel Per Inch**
109 dpi
- Brightness**
250 cd/m²
- Contrast Ratio**
 - Contrast Ratio: 3000:1
 - Dynamic Contrast Ratio (Typical): 3000000:1
- View Angle (H / V)**
Horizontal: 178°, Vertical: 178°
- Response Time**
 - Extreme Mode: 4 ms
 - Normal Mode: 6 ms
 - Off Mode: 14 ms
- Refresh Rate**
75Hz
- Color Gamut**
Coverage Ratio: 72% NTSC
- Color Support**
16.7 Million
- Color Depth**
8-bit
- Screen Surface Treatment**
Anti-glare

Operating System

- Operating System**
 - Windows® 11 Support
 - Windows® 10 Support

Power Supply

- Power Consumption**
 - Typical / Max: 28W / 35W
 - Sleep / Off mode: <0.5W
 - Switch-off Mode: <0.3W
 - Energy Star Power On: 27W
 - Energy Star TEC: 58kWh

Voltage Required
AC 90 to 264 V (50-60Hz)

Special Features

Special Features
AMD FreeSync™
AMD FreeSync™ technology only can work with AMD Radeon™ series graphics card.

DESIGN

Mechanical

ThinkCentre® M Series Support
ThinkCentre® M Series Tiny, ThinkCentre® M Series Nano
For supporting Tiny / Nano devices, additional Tiny / Nano VESA Mount Kits (PN: 4XFON03161) / (PN: 4XFOV81630) are needed (sold separately).

Bezel Width
• Side: 1.8mm
• Top / Bottom: 1.8mm / 28.1mm

Cable Management
Support

Case Color
OTS black

Dimensions (WxDxH)^[1]

Models	Dimensions
Highest Position	614.1 x 231.2 x 444.4 mm (24.18 x 9.10 x 17.49 inches)
Unpacked Head Only	614.1 x 43.7 x 374.5 mm (24.18 x 1.72 x 14.74 inches)

Packaging Dimensions (WxDxH)
717 x 179 x 453 mm (28.23 x 7.05 x 17.83 inches)

Weight^[2]

Models	Weight
Monitor With Stand	4.7 kg (10.4 lbs)
Monitor Head Only	4.1 kg (9.1 lbs)

Packaging Weight
6.6 kg (14.55 lbs)

Mounting
Supports VESA mount 100mm

Stand
Supports -5° to +22° tilt

- In the Box**
- Monitor with stand
 - 1x HDMI® cable (1.8m)
 - 1x Power cable (1.8m)
 - Quick setup guide
 - Warranty booklet

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Ports^[1]

Rear Ports

- 1x HDMI® 1.4
- 1x DisplayPort™ 1.4
- 1x Power Connector
- 1x audio-out (3.5mm)

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

Thunderbolt™ 5: 80 Gbit/s (bidirectional), up to 120 Gbit/s in bandwidth boost mode for video-intensive applications.

SECURITY & PRIVACY

Security

Physical Locks

Kensington® Security Slot™

SERVICE

Warranty

Base Warranty

3-year limited warranty

OPERATING REQUIREMENTS

Operating Environment

Temperature

Operating: 0°C to 40°C (32°F to 104°F)

Storage: -20°C to 60°C (-4°F to 140°F)

Relative Humidity

Operating: 8% to 80%

Storage: 5% to 95%

CERTIFICATIONS

Green Certifications^[1]

Green Certifications

- RoHS compliant
- Volatile Organic Compound Certification

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <https://compliance.lenovo.com>.

Other Certifications

Other Certifications

- TÜV Rheinland® Eye Comfort Certification

- TÜV Rheinland® Low Blue Light
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION “AS IS,” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

