

OVERVIEW



1.	Cable lock slot	3. 1x USB-C 3.1 Gen 1
2	. 1x USB-C 3.1 Gen 1	

Lenovo L15 - July 11 2024 1 of 6



PERFORMANCE

Panel

Panel

In-Plane Switching (IPS)

Backlight

WLED

Display Size

15.6 inches

Max View Area

WxH: 344.2 x 193.6 mm

Resolution

1920 x 1080

Aspect Ratio

16:9

Pixel Pitch

0.1793 x 0.1793 mm

Dot / Pixel Per Inch

141 dpi

Brightness

250 cd/m²

Contrast Ratio

- · Contrast Ratio: 1000:1
- Dynamic Contrast Ratio (Typical): 3000000:1

View Angle (H / V)

Horizontal: 178°, Vertical: 178°

Response Time

Extreme Mode: 6 msNormal Mode: 14 ms

Refresh Rate

60Hz

Color Gamut

45% NTSC

Color Support

16.7 Million

Color Depth

8-bit

Screen Surface Treatment

Anti-glare

Operating System

Operating System

- Windows® 11 Support
- Windows® 10 Support
- Windows® 7 Support

Power Supply

Power Consumption

- Typical / Max: 8W / 9.5W
- Sleep / Off mode: <0.3W
- Switch-off Mode: <0.3W

• External Power Supply

Voltage Required

Lenovo L15 - July 11 2024 2 of 6



DC 5 / 9 / 15 / 20 V

Special Features

Special Features

Lenovo® Artery (Lenovo® Accessories and Display Manager) Support

Lenovo® Artery supports Windows® 10 & 11, Mac OS, and Windows® On Arm (functions vary across systems).

Lenovo® Accessories and Display Manager is formerly Lenovo® Display Control Center.

DESIGN

Mechanical

Bezel Width

- Side: 7.3mm
- Top / Bottom: 7.3mm / 31.9mm

Cable Management

Support

Case Color

Grey (cover), raven black (bezel)

Dimensions (WxDxH)[1]

Models	Dimensions
Lowest Position	108.4 x 235.5 x 360.0 mm (42.67 x 9.27 x 14.17 inches)
Highest Position	108.4 x 245.5 x 360.0 mm (4.27 x 9.67 x 14.17 inches)

Packaging Dimensions (WxDxH)

279.9 x 407.9 x 75.9 mm (11.02 x 16.06 x 2.99 inches)

Weight^[2]

Models	Weight
Monitor With Stand	0.86 kg (1.90 lbs)

Packaging Weight

1.7 kg (3.75 lbs)

Mounting

Supports VESA mount 100mm, 2 screw holes

Stand

Supports up to 10mm lift

In the Box

- L15 Monitor
- 1x USB-C® to USB-C® cable (1m)
- 1x Pair of clips
- 1x Sleeve
- Quick setup guide

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Ports^[1]

Rear Ports

2x USB-C* 3.1 Gen 1 (DP 1.2 Alt Mode, one USB upstream, one USB downstream, USB 2.0 data transfer, up to 65W)

Lenovo L15 - July 11 2024 3 of 6



Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt[™] 3/4: 40 Gbit/s.

Thunderbolt[™] 5: 80 Gbit/s (bidirectional), up to 120 Gbit/s in bandwidth boost mode for video-intensive applications.

SECURITY & PRIVACY

Security

Physical Locks

Kensington® Security Slot™

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 3-year limited warranty

OPERATING REQUIREMENTS

Operating Environment

Temperature

Operating: 0°C to 40°C (32°F to 104°F) Storage: -20°C to 60°C (-4°F to 140°F)

Relative Humidity

Operating: 10% to 80% Storage: 5% to 95%

CERTIFICATIONS

Green Certifications^[1]

Green Certifications

- EPEAT™ Silver Registered^[2]
- RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit https://compliance.lenovo.com.

[2] EPEAT™ is registered where applicable, please visit epeat.net for registration status by country.

Other Certifications

Other Certifications

- TÜV Rheinland® Flicker Free
- TÜV Rheinland® Low Blue Light
- Feature with ** means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"

Lenovo L15 - July 11 2024 4 of 6

Lenovo L15



WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to vou.

• The specifications on this page may not be available in all regions, and may be changed or updated without notice.

Lenovo L15 - July 11 2024 5 of 6













Lenovo L15 - July 11 2024 6 of 6