

OVERVIEW



1. Joystick	5. HDMI
2. Source Key	6. VGA
3. Kensington Security Slot	7. Audio line-out (3.5mm)
4. Power connector	



PERFORMANCE

Panel

Panel

3-side NearEdgeless, In-Plane Switching

Backlight

WLED

Display Size

21.5 inches

Max View Area

WxH: 476.1 x 267.8 mm

Resolution

1920 x 1080

Aspect Ratio

16:9

Pixel Pitch

0.248 x 0.248 mm

Dot / Pixel Per Inch

102 dpi

Brightness

250 cd/m²

Contrast Ratio

· Contrast Ratio: 1000:1

• Dynamic Contrast Ratio (Typical): 3000000:1

View Angle (H / V)

Horizontal: 178°, Vertical: 178°

Response Time

Extreme Mode: 4 msNormal Mode: 6 ms

Off Mode: 14 ms

Refresh Rate

75Hz (HDMI® only)

Color Gamut

Coverage Ratio: 99% sRGB

Color Support

16.7 Million

Color Depth

8-bit

Screen Surface Treatment

Anti-glare

Operating System

Operating System

- Windows® 11 Support
- Windows® 10 Support

Multi-Media

Speakers

Stereo speakers, 3W x2

Power Supply

Power Consumption



Typical / Max: 15.3W / 21W

Sleep / Off mode: <0.5W

• Switch-off Mode: <0.3W

Internal Power Supply

Voltage Required

AC 100 to 240 V (50-60Hz)

Special Features

Special Features

- AMD FreeSync™
 - AMD FreeSync™ technology only can work with AMD Radeon™ series graphics card.
- Lenovo® Artery (Lenovo® Accessories and Display Manager) Support
 Lenovo® Artery supports Windows® 10 & 11, Mac OS, and Windows® On Arm (functions vary across systems).
 Lenovo® Accessories and Display Manager is formerly Lenovo® Display Control Center.
- · Natural Low Blue Light

DESIGN

Mechanical

ThinkCentre® M Series Support

ThinkCentre® M Series Tiny, ThinkCentre® M Series Nano For supporting Tiny / Nano devices, additional Tiny / Nano VESA Mount Kits (PN: 4XF0N03161) / (PN: 4XF0V81630) are needed (sold separately).

Bezel Width

- Side: 1.5mm
- Top / Bottom: 1.5mm / 22mm

Buttons

- Joystick
- Source Key

Cable Management

Support

Case Color

Storm grey

Dimensions (WxDxH)[1]

Models	Dimensions
Highest Position	488.0 x 178.9 x 407.3 mm (19.21 x 7.04 x 16.03 inches)
Lowest Position	488.0 x 178.9 x 407.3 mm (19.21 x 7.04 x 16.03 inches)
Unpacked Head Only	488.0 x 41.0 x 297.3 mm (19.21 x 7.04 x 16.03 inches)

Packaging Dimensions (WxDxH)

117 x 588 x 360 mm (4.61 x 23.15 x 14.17 inches)

Weight^[2]

Models	Weight
Monitor With Stand	2.9 kg (6.4 lbs)
Monitor Head Only	2.3 kg (5.1 lbs)

Packaging Weight

4.1 kg (9.04 lbs)

Mounting

Supports VESA mount 100mm

Stand

Supports -5° to +22° tilt

In the Box

Monitor with stand

Lenovo L22i-40



- 1x HDMI® cable (1.8m)
- 1x Power cable (1.8m)
- 1x Screw
- · Quick setup guide
- Warranty booklet

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Ports^[1]

Rear Ports

- 1x HDMI® 1.4
- 1x VGA
- 1x Power Connector
- 1x audio-out (3.5mm)

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

Thunderbolt™ 5: 80 Gbit/s (bidirectional), up to 120 Gbit/s in bandwidth boost mode for video-intensive applications.

SECURITY & PRIVACY

Security

Physical Locks

Kensington® Security Slot™

SERVICE

Warranty

Base Warranty

- 1-year courier or carry-in service
- 3-year limited warranty

OPERATING REQUIREMENTS

Operating Environment

Temperature

Operating: 0°C to 40°C (32°F to 104°F) Storage: -20°C to 60°C (-4°F to 140°F)

Relative Humidity

Operating: 8% to 80% Storage: 5% to 95%

CERTIFICATIONS



Green Certifications¹¹

Green Certifications

RoHS (2011/65/EU)

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit https://compliance.lenovo.com.

Other Certifications

Other Certifications

- Eyesafe® Certified 2.0
- TÜV Rheinland® Eye Comfort Certification
- TÜV Rheinland® Low Blue Light (Hardware Solution)
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.













