

OVERVIEW



1. Power connector	6. USB 3.2 Gen 1
2. HDMI 2.1 TMDS	7. USB 3.2 Gen 1
3. HDMI 2.1 TMDS	8. USB 3.2 Gen 1
4. DisplayPort 1.4	9. USB 3.2 Gen 1
5. USB-C 3.2 Gen 1 (DP 1.4 Alt Mode)	10. Audio-out (3.5mm)

PERFORMANCE

Panel

**Panel**  
3-side NearEdgeless, In-Plane Switching

**Backlight**  
WLED

**Display Size**  
27 inches

**Max View Area**  
WxH: 596.7 x 335.7 mm

**Resolution**  
2560 x 1440

**Aspect Ratio**  
16:9

**Pixel Pitch**  
0.233 x 0.233 mm

**Dot / Pixel Per Inch**  
109 dpi

**Brightness**  
400 cd/m<sup>2</sup>

**Contrast Ratio**

- Contrast Ratio: 1000:1
- Dynamic Contrast Ratio (Typical): 3000000:1

**View Angle (H / V)**  
Horizontal: 178°, Vertical: 178°

**Response Time**

- Moving Picture Response Time (MPRT) improves the response time and reduces motion blur in the monitor. Enabling MPRT will disable AMD FreeSync™™ technology, and may causes a negligible flicker.
- Moving Picture Response Time (MPRT): 0.5 ms
- Level 1: 4 ms
- Level 2: 3 ms
- Level 3: 2 ms
- Level 4: 1 ms
- Off Mode: 5 ms

**Refresh Rate**

- 165Hz (Overclock to 180Hz)  
Overclocking at 180Hz is based on laboratory test data, and this function may cause irregularities in the display
- HDMI®: 144Hz

**Color Gamut**

- Coverage Ratio: 99% sRGB
- Coverage Ratio: 95% DCI-P3
- Color Area Ratio: 126% sRGB

**Color Support**  
1.07 Billion

**Color Depth**  
10-bit (8-bit+FRC)

**Screen Surface Treatment**  
Anti-glare

Operating System

**Operating System**

- Windows® 11 Support

- Windows® 10 Support

Multi-Media

Camera

No bundled webcam (Support Lenovo® LC 50 Monitor Webcam, sold separately)

Speakers

Integrated Speakers, 3W x2

Power Supply

Power Consumption

- Typical / Max: 88W / 160W
- Sleep / Off mode: <0.5W
- Switch-off Mode: <0.3W
- Internal Power Supply

Voltage Required

AC 100 to 240 V (50-60Hz)

Special Features

Special Features

- DisplayHDR™ 400
- Factory Calibration: Avg. Delta E<2
- Processor LUT: 10 bit
- AMD FreeSync™ Premium  
AMD FreeSync™ technology only can work with AMD Radeon™ series graphics card.
- Lenovo® Artery (Lenovo® Accessories and Display Manager) Support  
Lenovo® Artery supports Windows® 10 & 11, Mac OS, and Windows® On Arm (functions vary across systems).  
Lenovo® Accessories and Display Manager is formerly Lenovo® Display Control Center.
- Adaptive Sync
- Gaming Console Support
- Natural Low Blue Light
- Smart Power  
The Smart Power function intelligently detects overall power consumption and dynamically manages the power delivery to each device

DESIGN

Mechanical

Bezel Width

- Side: 2.0mm
- Top / Bottom: 2mm / 20.6mm

Cable Management

Support

Case Color

Raven black

Dimensions (WxDxH)<sup>[1]</sup>

Models	Dimensions
Lowest Position	613.7 x 258.8 x 401.5 mm (24.16 x 10.19 x 15.81 inches)
Highest Position	613.7 x 258.8 x 536.5 mm (24.16 x 10.19 x 21.12 inches)
Unpacked Head Only	613.7 x 61 x 365.9 mm (24.16 x 2.4 x 14.41 inches)

Packaging Dimensions (WxDxH)

160 x 720 x 510 mm (6.30 x 28.35 x 20.08 inches)

Weight<sup>[2]</sup>

Models	Weight
Monitor With Stand	6.8 kg (15.0 lbs)

Monitor Head Only	4.8 kg (10.6 lbs)
-------------------	-------------------

**Packaging Weight**

9.8 kg (21.61 lbs)

**Mounting**

Supports VESA mount 100mm

**Stand**

Supports -5° to +25° tilt, left & right 30° swivel, -90° to +90° pivot, up to 135mm lift

**In the Box**

- Monitor with stand
- 1x DP cable (1.8m)
- 1x USB-C® to USB-C® cable (1m)
- 1x Power cable (1.8m)
- Factory calibration report
- Quick setup guide
- Warranty booklet

Notes:

- [1] The system dimensions may vary depending on configurations.
- [2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Ports<sup>[1]</sup>

Rear Ports<sup>[2]</sup>

- 1x USB-C® 3.2 Gen 1 (DP 1.4 Alt Mode and up to 75W PD), USB upstream
- 4x USB 3.2 Gen 1, USB downstream
- 2x HDMI® 2.1 TMDS<sup>[3]</sup>
- 1x DisplayPort™ 1.4
- 1x Power Connector
- 1x audio-out (3.5mm)

Notes:

- [1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.
- USB 2.0: 480 Mbit/s;
- USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
- USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
- USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
- USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;
- Thunderbolt™ 3/4: 40 Gbit/s.
- Thunderbolt™ 5: 80 Gbit/s (bidirectional), up to 120 Gbit/s in bandwidth boost mode for video-intensive applications.
- [2] Up to 75W power delivery to compatible devices by USB-C®. Listed as maximum capacity of power delivery. Actual capacity of power delivery may vary depending upon devices connected or monitor configuration, and may decline with downstream USB ports connected or higher brightness setting.
- [3] Supports 2560x1440@144Hz as specified in HDMI® 2.1.

SECURITY & PRIVACY

Security

Physical Locks

Kensington® Security Slot™

SERVICE

## Warranty

### Base Warranty

3-year limited warranty

## OPERATING REQUIREMENTS

### Operating Environment

#### Temperature

Operating: 0°C to 40°C (32°F to 104°F)

Storage: -20°C to 60°C (-4°F to 140°F)

#### Relative Humidity

Operating: 8% to 80%

Storage: 5% to 95%

## CERTIFICATIONS

### Green Certifications<sup>[1]</sup>

#### Green Certifications

- RoHS compliant
- Volatile Organic Compound Certification

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <https://compliance.lenovo.com>.

### Other Certifications

#### Other Certifications

- Eyesafe® Certified
  - TÜV Rheinland® Eye Comfort Certification
  - TÜV Rheinland® Low Blue Light (Hardware Solution)
- 
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
  - The specifications on this page may not be available in all regions, and may be changed or updated without notice.

