

OVERVIEW





1. SD card reader	6. USB 3.2 Gen 1 (Always On)
2. USB 3.2 Gen 1	7. HDMI
3. Ethernet (RJ-45)	8. Thunderbolt 4
4. Kensington Nano Security Slot	9. Headphone / microphone combo jack (3.5mm)
5. USB-C 3.2 Gen 2	



PERFORMANCE

Processor

Processor Family

13th Generation Intel® U, P or H Series Core i3 / i5 / i7 Processor

Processor**

Processor Name	Cores Thi		Max Frequency	Cache	Processor Graphics	
Core i3-1315U	6 (2 P-core + 4 E- core)		P-core 4.5GHz / E-core 3.3GHz	10MB Intel® Smart Cache	Intel® UHD Graphics	
Core i5-1334U	10 (2 P-core + 8 E-		P-core 4.6GHz / E-core	12MB Intel® Smart	Intel® Iris® Xe	
	core) 12		3.4GHz	Cache	Graphics[1]	
Core i5-1335U	335U 10 (2 P-core + 8 E-		P-core 4.6GHz / E-core	12MB Intel® Smart	Intel® Iris® Xe	
	core) 12		3.4GHz	Cache	Graphics[2]	
Core i5-1340P	Core i5-1340P 12 (4 P-core + 8 E-		P-core 4.6GHz / E-core	12MB Intel® Smart	Intel® Iris® Xe	
	core) 16		3.4GHz	Cache	Graphics[3]	
Core i5- 13420H 8 (4 P-core + 4 E- core) 12		12	P-core 4.6GHz / E-core 3.4GHz	12MB Intel® Smart Cache	Intel® UHD Graphics	
Core i5-	1 16		P-core 4.7GHz / E-core	18MB Intel® Smart	Intel® Iris® Xe	
13500H			3.5GHz	Cache	Graphics[4]	
Core i7-1355U	10 (2 P-core + 8 E- core)	12	P-core 5.0GHz / E-core 3.7GHz	12MB Intel® Smart Cache	Intel® Iris® Xe Graphics ^[5]	
Core i7-1360P 12 (4 P-core + 8 E-core) 16		P-core 5.0GHz / E-core	18MB Intel® Smart	Intel® Iris® Xe		
		3.7GHz	Cache	Graphics ^[6]		
Core i7- 13700H 14 (6 P-core + 8 E- core) 20		P-core 5.0GHz / E-core 3.7GHz	24MB Intel® Smart Cache	Intel® Iris® Xe Graphics[7]		

Notes:

[1], [2], [3], [4], [5], [6], [7] Intel® Iris® Xe Graphics capability requires system to be configured with dual-channel memory. On the system with single-channel memory, Intel® Iris® Xe Graphics will function as Intel® UHD Graphics.

Operating System

Operating System**

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- No preload operating system

Graphics

Graphics**

Graphics	Туре	Memory	TGP	Key Features	
Intel® UHD Graphics	Integrated	Shared	Share CPU TDP	DirectX® 12.1	
Intel® Iris® Xe Graphics[1]	Integrated	Shared	Share CPU TDP	DirectX® 12.1	

Notes:

[1] Intel® Iris® Xe Graphics capability requires system to be configured with dual-channel memory. On the system with single-channel memory, Intel® Iris® Xe Graphics will function as Intel® UHD Graphics.

Monitor Support

Monitor Support

Supports up to 4 independent displays (native display and 3 external monitors via HDMI®, USB-C® and Thunderbolt™)

- HDMI® supports up to 3840x2160@60Hz
- USB-C® supports up to 5120x2880@60Hz
- Thunderbolt™ supports up to 5120x2880@60Hz



Chipset

Chipset

Intel® SoC (System on Chip) platform

Memory

Max Memory[1]

Up to 64GB DDR5-5200

Memory Slots

Two DDR5 SODIMM slots, dual-channel capable

Memory Type

DDR5-5200^[2]

Notes:

- [1] The max memory is based on the technical readiness of the system. Available memory to sell would vary.
- [2] Installed memory is actually DDR5-5600 but runs as DDR5-5200 due to platform limitation.

Storage

Max Storage Support[1]

Up to two drives, 2x M.2 SSD

- M.2 2242 SSD up to 1TB
- M.2 2280 SSD up to 2TB

Storage Slot[2]

Two M.2 2280 PCIe® 4.0 x4 slots

Storage Type***

Disk Type	Interface	Offering
M.2 2242 SSD	PCle® NVMe®, PCle® 4.0 x4	256GB / 512GB / 1TB
M.2 2280 SSD	PCle® NVMe®, PCle® 4.0 x4	512GB / 1TB

Notes:

[1] The system supports dual SSD via two M.2 slots, but Lenovo® only offers one SSD configuration, another SSD slot for user self-extension.

The max storage capacity is only technical readiness and may be different from current Lenovo® storage offerings.

[2] The actual data transfer rate of the following PCIe® interface also depends on the capabilities of the connected PCIe® device. The listed values represent theoretical maximums.

PCIe[®] 3.0 (x2 / x4): 2 GB/s (16 Gbps) / 4 GB/s (32 Gbps);

PCIe[®] 4.0 (x2 / x4): 4 GB/s (32 Gbps) / 8 GB/s (64 Gbps);

PCIe[®] 5.0 (x2 / x4): 8 GB/s (64 Gbps) / 16 GB/s (128 Gbps).

Removable Storage

Card Reader

SD card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Stereo speakers, 2W x2, Dolby Audio™

Microphone

Dual-microphone array with smart noise-cancelling

Camera**

- HD 720p, with privacy shutter, fixed focus
- FHD 1080p + IR hybrid, with privacy shutter, fixed focus
- FHD 1080p, with privacy shutter, fixed focus



Battery

Battery**

- 45Wh Rechargeable Li-ion Battery, supports Rapid Charge Pro (charge up to 50% in 30min)
- 60Wh Rechargeable Li-ion Battery, supports Rapid Charge (charge up to 80% in 1hr)

Max Battery Life[1]

 Models with 45Wh battery: MobileMark® 2018: 9.03 hr MobileMark® 25: 8.68 hr

Local video (1080p) playback@150nits: 13.78 hr

 Models with 60Wh battery: MobileMark® 2018: 11.4 hr MobileMark® 25: 12.1 hr

Local video (1080p) playback@150nits: 16.53 hr

Notes:

[1] All battery life claims are approximate maximum and based on results using the MobileMark® 2018, MobileMark® 25, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter**[1]

- 65W USB-C[®] (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim (wall-mount) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 100W USB-C® slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

Notes:

[1] AC adapter offerings depend on the country.

Special Features

Special Features

Modern Standby

DESIGN

Display

Display**[1]

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Refresh Rate	Viewing Angle (L/R/U/D)	Key Features
14"	WUXGA (1920x1200)	Non- touch	IPS	300nits	Anti- glare	16:10	1000:1	45% NTSC	60Hz	89° / 89° / 89° / 89° /	TÜV Low Blue Light (Software)
14"	WUXGA (1920x1200)	Multi- touch	IPS	300nits	Anti- glare	16:10	1000:1	45% NTSC	60Hz	89° / 89° / 89° / 89° /	TÜV Low Blue Light (Software)
14"	WUXGA (1920x1200)	Non- touch	IPS	300nits	Anti- glare	16:10	1000:1	100% sRGB	60Hz	89° / 89° / 89° / 89°	Eyesafe® Certified 2.0
14"	2.2K (2240x1400)	Non- touch	IPS	300nits	Anti- glare	16:10	1200:1	100% sRGB	60Hz	89° / 89° / 89° / 89°	Eyesafe® Certified 2.0

Touchscreen

- · Add-on Film Touch, supports 10-point touch
- · Non-touch

Screen-to-Body Ratio



90%

Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Input Device

Pen

No support

Keyboard

6-row, spill-resistant, multimedia Fn keys, key travel 1.5mm

Keyboard Backlight

- · LED backlight
- · Non-backlight

Touchpad

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 75 x 120 mm (2.95 x 4.72 inches)

Mechanical

Dimensions (WxDxH)[1]

313.5 x 224 x 16.9 mm (12.34 x 8.82 x 0.67 inches)

Weight^[2]

Starting at 1.38 kg (3.04 lbs)

Case Color

Arctic grey, dual-tone design

Case Material

Aluminium (top), aluminium (bottom)

Surface Treatment

Anodizing sandblasting

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

WLAN + Bluetooth®**[1]

- Wi-Fi[®] 6, 802.11ax 2x2 Wi-Fi[®] + Bluetooth[®] 5.2, M.2 card
- Wi-Fi® 6E, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3, Intel® vPro® technology support, M.2 card[2]
- Wi-Fi® 6E, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3, M.2 card

WWAN

No support

Ethernet**[3]

- Gigabit Ethernet, Intel® Ethernet Connection I219-LM (vPro® models), 1x RJ-45, supports Wake-on-LAN
- Gigabit Ethernet, Intel® Ethernet Connection I219-V (non-vPro® models), 1x RJ-45, supports Wake-on-LAN

Notos

[1] Wi-Fi® operation (including Wi-Fi® 6, Wi-Fi® 6E, Wi-Fi® 7, etc.) is subject to the regulatory requirements of each country. Bluetooth® may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.

[2] Intel® vPro® platform requires the hardware and software necessary to deliver the manageability use cases, security features, system performance, and stability that define the platform. For detailed vPro® support information, please refer to the System Management section.



[3] Wake-on-LAN needs the power adapter plugged in.

Ports^[1]

Standard Ports

- 1x USB 3.2 Gen 1
- 1x USB 3.2 Gen 1 (Always On)
- 1x USB-C® 3.2 Gen 2 (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.4)
- 1x Thunderbolt™ 4 / USB4® 40Gbps (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.4)
- 1x HDMI[®] 2.1, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Ethernet (RJ-45)
- 1x SD card reader

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

Thunderbolt™ 5: 80 Gbit/s (bidirectional), up to 120 Gbit/s in bandwidth boost mode for video-intensive applications.

Docking

Docking

Various docking solutions supported via Thunderbolt™ or USB-C®.

For more compatible docking solutions, please visit Docking for ThinkBook® 14 G6 IRL

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in SoC

Physical Locks

Kensington® Nano Security Slot™, 2.5 x 6 mm

Fingerprint Reader

Touch style fingerprint reader integrated in smart power button

BIOS Security

- · Hard disk password
- Power-on password
- · Supervisor password
- Self-healing BIOS

Other Security

- Camera privacy shutter
- (Optional) IR camera for Windows® Hello (facial recognition)

MANAGEABILITY

System Management

System Management[1]

- Intel® vPro® Essentials^[2]
- Non-vPro®

Notes:

[1] Intel® vPro® platform require an eligible Intel® processor, a supported operating system, Intel® LAN and/or WLAN



silicon, firmware enhancements, and other hardware and software necessary to deliver the manageability use cases, security features, system performance, and stability that define the platform. See Intel® vPro® Platform for details.

[2] Intel® vPro® offers a superset of DASH's defined capabilities.

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- · 2-year (1-yr battery) courier or carry-in service
- · No base warranty

ACCESSORIES

Bundled Accessories

Bundled Accessories[1]

- Lenovo® 15.6" laptop casual toploader, polyester
- None

Notes:

[1] For more compatible accessory solutions, please visit Accessories for ThinkBook® 14 G6 IRL.

OPERATING REQUIREMENTS

Operating Environment

Temperature[1]

- At altitudes up to 2438 m (8.000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
 - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Δltitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

ENVIRONMENTAL

Sustainability

Material^[1]

25% PCC recycled plastic used in the battery pack enclosure

50% PCC recycled plastic used in key caps

90% PCC recycled plastic used in standard 65W and 100W adapter

95% recycled content in PIC cushion

30% recycled content in OBP bag

FSC certified content in carton box

Notes:

[1] PCC: Post Consumer Content, recycled materials from customers.

CERTIFICATIONS



Green Certifications¹¹

Green Certifications[2]

- ENERGY STAR® 9.0
- EPEAT™ Gold Registered^[3]
- ErP Lot 6/26
- FSC certified package
- · RoHS compliant
- TCO Certified 9.0^[4]

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit https://compliance.lenovo.com.

[2] EPEAT™ registration and ENERGY STAR® certification are optional and only available on the models with preloaded OS. Please visit <u>epeat.net</u> and <u>energystar.gov</u> for more information.

[3] EPEAT™ is registered where applicable, please visit epeat.net for registration status by country.

[4] TCO certification is NOT available in India and Brazil.

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed

Other Certifications

- (Optional) Eyesafe® Certified 2.0
- (Optional) Intel® Evo™ Platform
- (Optional) TÜV Rheinland® Low Blue Light (Hardware Solution)
- (Optional) TÜV Rheinland® Low Blue Light (Software Solution)
- Feature with ** means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Feature with *** means that one or more options listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.













