

OVERVIEW



| | |
|----------------------------------|--|
| 1. SD card reader | 6. USB 3.2 Gen 1 (Always On) |
| 2. USB 3.2 Gen 1 | 7. HDMI |
| 3. Ethernet (RJ-45) | 8. USB-C 3.2 Gen 2 |
| 4. Kensington Nano Security Slot | 9. Headphone / microphone combo jack (3.5mm) |
| 5. USB-C 3.2 Gen 2 | |

PERFORMANCE

Processor

Processor Family

AMD Ryzen™ 3 / 5 / 7 Processor

Processor**

| Processor Name | Cores | Threads | Base Frequency | Max Frequency | Cache | Processor Graphics |
|--------------------|-------|---------|----------------|---------------|------------------|----------------------|
| AMD Ryzen™ 3 7330U | 4 | 8 | 2.3GHz | 4.3GHz | 2MB L2 / 8MB L3 | AMD Radeon™ Graphics |
| AMD Ryzen™ 5 7430U | 6 | 12 | 2.3GHz | 4.3GHz | 3MB L2 / 16MB L3 | AMD Radeon™ Graphics |
| AMD Ryzen™ 5 7530U | 6 | 12 | 2.0GHz | 4.5GHz | 3MB L2 / 16MB L3 | AMD Radeon™ Graphics |
| AMD Ryzen™ 7 7730U | 8 | 16 | 2.0GHz | 4.5GHz | 4MB L2 / 16MB L3 | AMD Radeon™ Graphics |

Operating System

Operating System**

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- No preload operating system

Graphics

Graphics

| Graphics | Type | Memory | TGP | Key Features |
|----------------------|------------|--------|---------------|--------------|
| AMD Radeon™ Graphics | Integrated | Shared | Share CPU TDP | DirectX® 12 |

Monitor Support

Monitor Support

Supports up to 4 independent displays (native display and 3 external monitors via HDMI® and USB-C®). More external displays can be supported via docking or daisy chain.

- HDMI® supports up to 3840x2160@60Hz
- USB-C® supports up to 3840x2160@60Hz

Chipset

Chipset

AMD SoC (System on Chip) platform

Memory

Max Memory^[1]

Up to 64GB DDR4-3200

Memory Slots

Two DDR4 SO-DIMM slots, dual-channel capable

Memory Type

DDR4-3200

Notes:

^[1] The max memory is based on the technical readiness of the system. Available memory to sell would vary.

Storage

Max Storage Support^[1]

Up to two drives, 2x M.2 SSD

- M.2 2242 SSD up to 1TB
- M.2 2280 SSD up to 2TB

Storage Slot^[2]

Two M.2 2280 PCIe® 3.0 x4 slots

Storage Type^{***[3]}

| Disk Type | Interface | Offering |
|--------------|--|---------------------|
| M.2 2242 SSD | PCIe [®] NVMe [®] , PCIe [®] 3.0 x4 | 128GB |
| M.2 2242 SSD | PCIe [®] NVMe [®] , PCIe [®] 4.0 x4 | 256GB / 512GB / 1TB |
| M.2 2280 SSD | PCIe [®] NVMe [®] , PCIe [®] 4.0 x4 | 512GB / 1TB / 2TB |

Notes:

[1] The system supports dual SSD via two M.2 slots, but Lenovo[®] only offers one SSD configuration, another SSD slot for user self-extension.
The max storage capacity is only technical readiness and may be different from current Lenovo[®] storage offerings.

[2] The actual data transfer rate of the following PCIe[®] interface also depends on the capabilities of the connected PCIe[®] device. The listed values represent theoretical maximums.
PCIe[®] 3.0 (x2 / x4): 2 GB/s (16 Gbps) / 4 GB/s (32 Gbps);
PCIe[®] 4.0 (x2 / x4): 4 GB/s (32 Gbps) / 8 GB/s (64 Gbps);
PCIe[®] 5.0 (x2 / x4): 8 GB/s (64 Gbps) / 16 GB/s (128 Gbps).

[3] The SSD with PCIe[®] 4.0x4 is downgraded to closer to PCIe[®] 3.0 x4 due to AMD platform limitations.

Removable Storage

Card Reader
SD card reader

Multi-Media

Audio Chip
High Definition (HD) Audio, Realtek[®] ALC3287 codec

Speakers
Stereo speakers, 2W x2, Dolby Audio[™]

Microphone
Dual-microphone array with smart noise-cancelling

Camera^{**}

- HD 720p, with privacy shutter, fixed focus
- FHD 1080p + IR hybrid, with privacy shutter, fixed focus
- FHD 1080p, with privacy shutter, fixed focus

Battery

Battery^{**}

- 45Wh Rechargeable Li-ion Battery, supports Rapid Charge Pro (charge up to 50% in 30min)
- 71Wh Rechargeable Li-ion Battery

Max Battery Life^[1]

- Models with 45Wh battery:
MobileMark[®] 2018: 9.22 hr
MobileMark[®] 25: 9.42 hr
Local video (1080p) playback@150nits: 13.2 hr
- Models with 71Wh battery:
MobileMark[®] 2018: 14.12 hr
MobileMark[®] 25: 15.27 hr
Local video (1080p) playback@150nits: 17.13 hr

Notes:

[1] All battery life claims are approximate maximum and based on results using the MobileMark[®] 2018, MobileMark[®] 25, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter^{**[1]}

- 65W USB-C® (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim (wall-mount) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

Notes:

[1] AC adapter offerings depend on the country.

Special Features

Special Features

Modern Standby

DESIGN

Display

Display**[1]

| Size | Resolution | Touch | Type | Brightness | Surface | Aspect Ratio | Contrast Ratio | Color Gamut | Refresh Rate | Viewing Angle (L/R/U/D) | Key Features |
|------|-------------------|-------------|------|------------|------------|--------------|----------------|-------------|--------------|-------------------------|-------------------------------|
| 16" | WUXGA (1920x1200) | Multi-touch | IPS | 300nits | Anti-glare | 16:10 | 1000:1 | 45% NTSC | 60Hz | 89° / 89° / 89° / 89° | TÜV Low Blue Light (Software) |
| 16" | WUXGA (1920x1200) | Non-touch | IPS | 300nits | Anti-glare | 16:10 | 1000:1 | 45% NTSC | 60Hz | 89° / 89° / 89° / 89° | TÜV Low Blue Light (Software) |
| 16" | WQXGA (2560x1600) | Non-touch | IPS | 350nits | Anti-glare | 16:10 | 1200:1 | 100% sRGB | 60Hz | 89° / 89° / 89° / 89° | Eyesafe® Certified 2.0 |

Touchscreen

- On-cell multi-touch, supports 10-point touch
- Non-touch

Screen-to-Body Ratio

90%

Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Input Device

Pen

No support

Keyboard

6-row, spill-resistant, multimedia Fn keys, numeric keypad, key travel 1.5mm

Keyboard Backlight

- LED backlight
- Non-backlight

Touchpad

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 75 x 120 mm (2.95 x 4.72 inches)

Mechanical

Dimensions (WxDxH)[1]

356 x 253.5 x 17.5 mm (14.01 x 9.98 x 0.69 inches)

Weight[2]

Starting at 1.7 kg (3.75 lbs)

Case Color

Arctic grey, dual-tone design

Case Material

Aluminium (top), PC-ABS (bottom)

Surface Treatment

Anodizing sandblasting

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

WLAN + Bluetooth®**[1]

- Wi-Fi® 6, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3, M.2 card^[2]
- Wi-Fi® 6E, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3, M.2 card^[3]

WWAN

No support

Ethernet^[4]

Gigabit Ethernet, 1x RJ-45, supports Wake-on-LAN

Notes:

[1] Bluetooth® may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.

[2] Wi-Fi® 6 full features might be limited by country-level restrictions.

[3] Wi-Fi® 6E full features might be limited by country-level restrictions.

6GHz Wi-Fi® 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi® 6E, and the regional regulatory certifications & spectrum allocation.

[4] Wake-on-LAN needs the power adapter plugged in.

Ports

Standard Ports

- 1x USB 3.2 Gen 1
- 1x USB 3.2 Gen 1 (Always On)
- 2x USB-C® 3.2 Gen 2 (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.4)
- 1x HDMI® 2.1, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Ethernet (RJ-45)
- 1x SD card reader

Docking

Docking

Various docking solutions supported via USB-C®.

For more compatible docking solutions, please visit [Docking for ThinkBook® 16 G6 ABP](#)

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in SoC

Physical Locks

Kensington® Nano Security Slot™, 2.5 x 6 mm

Fingerprint Reader

Touch style fingerprint reader integrated in smart power button

BIOS Security

- Hard disk password

- Power-on password
- Supervisor password
- Self-healing BIOS

Other Security

- Camera privacy shutter
- (Optional) IR camera for Windows® Hello (facial recognition)

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 2-year (1-yr battery) courier or carry-in service

ACCESSORIES

Bundled Accessories

Bundled Accessories^[1]

None

Notes:

[1] For more compatible accessory solutions, please visit [Accessories for ThinkBook® 16 G6 ABP](#).

OPERATING REQUIREMENTS

Operating Environment

Temperature^[1]

- At altitudes up to 2438 m (8,000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
 - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

ENVIRONMENTAL

Sustainability

Material^[1]

25% PCC recycled plastic used in the battery pack enclosure
50% PCC recycled plastic used in key caps
90% PCC recycled plastic used in standard 65W adapter
95% recycled content in PIC cushion
30% recycled content in OBP bag
FSC certified content in carton box

Notes:

[1] PCC: Post Consumer Content, recycled materials from customers.

CERTIFICATIONS

Green Certifications^[1]

Green Certifications^[2]

- ENERGY STAR® 8.0
- EPEAT™ Gold Registered^[3]
- ErP Lot 6/26
- FSC certified package
- RoHS compliant
- TCO Certified 9.0^[4]

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <https://compliance.lenovo.com>.

[2] EPEAT™ registration and ENERGY STAR® certification are optional and only available on the models with preloaded OS. Please visit epeat.net and energystar.gov for more information.

[3] EPEAT™ is registered where applicable, please visit epeat.net for registration status by country.

[4] TCO certification is NOT available in India and Brazil.

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed

Other Certifications

- (Optional) Eyesafe® Certified 2.0
- (Optional) TÜV Rheinland® Low Blue Light (Hardware Solution)
- (Optional) TÜV Rheinland® Low Blue Light (Software Solution)

- Feature with ** means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Feature with *** means that one or more options listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.



AMD



AMD



AMD



AMD



AMD



AMD