



OVERVIEW





1. Power button	11. Serial *
2. Card reader *	12. VGA
3. Microphone jack (3.5mm)	13. Ethernet (RJ-45)
4. Headphone / microphone combo jack (3.5mm)	14. 2x USB 2.0
5. USB-C 3.2 Gen 1 (support data transfer and 5V@3A charging)	15. USB 3.2 Gen 1 (with Smart Power On)
6. 2x USB 3.2 Gen 1	16. USB 3.2 Gen 1
7. Optical drive *	17. Serial *
8. Line-out (3.5mm)	18. Optional ports on expansion cards *
9. HDMI	19. Power connector
10. DisplayPort 1.4	

Notes:

- Items with * are only available on selected models
- Onboard video ports are only available for the models with integrated graphics



PERFORMANCE

Processor

Processor Family

Intel® Celeron®, Intel® Pentium®, or 12th Generation Intel® Core™ i3 / i5 / i7 / i9 Processor

Processor**

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics
Celeron® G6900	2	2	3.4GHz	-	4MB	Intel® UHD Graphics 710
Pentium® Gold G7400	2	4	3.7GHz	-	6МВ	Intel® UHD Graphics 710
Core i3-12100	4 (4 P-core + 0 E-core)	8	P-core 3.3GHz	P-core 4.3GHz ^[1]	12MB	Intel® UHD Graphics 730
Core i3-12300	4 (4 P-core + 0 E-core)	8	P-core 3.5GHz	P-core 4.4GHz ^[2]	12MB	Intel® UHD Graphics 730
Core i5-12400	6 (6 P-core + 0 E-core)	12	P-core 2.5GHz	P-core 4.4GHz ^[3]	18MB	Intel® UHD Graphics 730
Core i5-12400F	6 (6 P-core + 0 E-core)	12	P-core 2.5GHz	P-core 4.4GHz ^[4]	18MB	-
Core i5-12500	6 (6 P-core + 0 E-core)	12	P-core 3.0GHz	P-core 4.6GHz ^[5]	18MB	Intel® UHD Graphics 770
Core i5-12600	6 (6 P-core + 0 E-core)	12	P-core 3.3GHz	P-core 4.8GHz ^[6]	18MB	Intel® UHD Graphics 770
Core i7-12700	12 (8 P-core + 4 E-core)	20	P-core 2.1GHz / E- core 1.6GHz	Max Turbo up to 4.9GHz / P-core 4.8GHz / E-core 3.6GHz ^[7]	25MB	Intel® UHD Graphics 770
Core i7-12700F	12 (8 P-core + 4 E-core)	20	P-core 2.1GHz / E- core 1.6GHz	Max Turbo up to 4.9GHz / P-core 4.8GHz / E-core 3.6GHz ^[8]	25MB	-
Core i9-12900	16 (8 P-core + 8 E-core)	24	P-core 2.4GHz / E- core 1.8GHz	Max Turbo up to 5.1GHz / P-core 5.0GHz / E-core 3.8GHz ^[9]	зомв	Intel® UHD Graphics 770
Core i9-12900F	16 (8 P-core + 8 E-core)	24	P-core 2.4GHz / E- core 1.8GHz	Max Turbo up to 5.1GHz / P-core 5.0GHz / E-core 3.8GHz ^[10]	зомв	-

Notes:

[1], [2], [3], [4], [5], [6], [7], [8], [9], [10] Intel® Max Turbo frequency will vary depending on application workload and the hardware and software configurations, see

http://www.intel.com/technology/turboboost/ for more information.

Operating System

Operating System**

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- Windows® 11 DG Windows® 10 Pro 64
- Ubuntu Linux[1]
- No preload operating system

Notes:

[1] Some features may not be supported on the system with Linux preload, including but not limited to Intel® RST RAID, Human Presence Detection, etc.

Graphics

Graphics***[1]

Graphic	Туре	Memory	Max Resolution	Connector	Key Features
---------	------	--------	----------------	-----------	--------------



Intel® UHD graphics 710	Integrated	Shared	3840×2160@60Hz(HDMI®), 1920x1200@60Hz(VGA), 4096x2304@60Hz(DP)	1x HDMI® 2.1 TMDS, 1x VGA, 1x DP 1.4 HBR2	DirectX® 12
Intel® UHD graphics 730	Integrated	Shared	3840×2160@60Hz(HDMI®), 1920x1200@60Hz(VGA), 4096x2304@60Hz(DP)	1x HDMI® 2.1 TMDS, 1x VGA, 1x DP 1.4 HBR2	DirectX® 12
Intel® UHD graphics 770	Integrated	Shared	3840×2160@60Hz(HDMI®), 1920x1200@60Hz(VGA), 4096x2304@60Hz(DP)	1x HDMI® 2.1 TMDS, 1x VGA, 1x DP 1.4 HBR2	DirectX® 12
Intel® Iris® Xe MAX 100 Graphics ^[2]	Discrete	2GB LPDDR4X	3840x2160@30Hz(HDMI®), 1920x1080@60Hz(VGA)	1x VGA, 1x HDMI® 1.4	DirectX® 12, OpenGL 4.6

Notes:

[1] The information of integrated graphics are not applicable for the models with processor which has no integrated graphics inside (for the details, please refer to processor section).

[2] Onboard video ports are only available for the models with integrated graphics.

Monitor Support

Monitor Support

Supports up to 3 independent displays via (HDMI®, DP and VGA), more displays support via discrete graphics

Chipset

Chipset

Intel® B660 chipset

Memory

Max Memory[1]

Up to 64GB DDR4-3200

Memory Slots

Two DDR4 UDIMM slots, dual-channel capable

Memory Type

DDR4-3200

Notes:

[1] The max memory is based on the test results with current Lenovo® memory offerings.

Storage

Storage Support[1]

Up to two drives, 1x 2.5"/3.5" HDD + 1x M.2 SSD

- 2.5" HDD up to 1TB
- 3.5" HDD up to 2TB
- M.2 SSD up to 1TB

Storage Type***

Disk Type	Interface	RPM	Security
2.5" SATA HDD	SATA 6Gb/s	7.2K	-
3.5" SATA HDD	SATA 6Gb/s	7.2K	-
M.2 2242 SSD	PCle® NVMe®, PCle® 3.0 x4	-	-
M.2 2280 SSD	PCle® NVMe®, PCle® 3.0 x4	-	Opal 2.0
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4	-	Opal 2.0

RAID

No support

Notes:



[1] The max capacity of each disk type is based on the test results with current Lenovo® storage offerings.

Removable Storage

Optical**

- DVD-ROM, SATA 1.5Gb/s, slim (9.0mm)
- DVD burner (DVD±RW), SATA 1.5Gb/s, slim (9.0mm)
- None

Card Reader

- 7-in-1 card reader (SD, SDHC, SDXC, MMC, MS, MS-Pro, XD)
- No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC623-CG codec

Speakers

- No speakers
- Single speaker, 1W x1

Power Supply

Power Supply**

Power	Туре	Efficiency	Key Features
180W	Fixed	85%	Autosensing
260W	Fixed	90%	Autosensing

DESIGN

Input Device

Keyboard**

- Lenovo® Calliope Keyboard (USB connector), black
- Lenovo® Calliope Wireless Keyboard, black
- Lenovo® Traditional Keyboard (USB connector), black
- No keyboard

Mouse**

- Lenovo® Calliope Mouse (USB connector), black
- Lenovo® Calliope Wireless Mouse (2.4GHz via USB receiver), black
- · No mouse

Mechanical

Form Factor

SFF (7.4L)

Dimensions (WxDxH)[1]

100 x 308 x 274.8 mm (3.9 x 12.1 x 10.8 inches)

Packaging Dimensions (WxDxH)

195 x 390 x 500 mm (7.67 x 15.35 x 19.69 inches)

Weight^[2]

Around 4.5 kg (9.9 lbs)

Packaging Weight

Around 6.35 kg (14 lbs)

Case Color

Raven black

Bays

- 1x 2.5"/3.5" disk bay
- · 1x slim ODD bay



Expansion Slots

- One PCIe® 4.0 x16, low-profie (length < 167.65mm, height < 68.90mm)
- One PCle® 3.0 x1, low-profie (length < 167.65mm, height < 68.90mm)
- Two M.2 slots (one for WLAN, one for SSD)

EOU

No support

Stand

- · Vertical stand
- No stand

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

WLAN + Bluetooth®**

- Realtek® RTL8822CE, Wi-Fi® 5, 802.11ac Dual Band 2x2 Wi-Fi® + Bluetooth® 5.0, M.2 card
- Intel® Wireless-AC 9560, Wi-Fi® 5, 802.11ac Dual Band 2x2 Wi-Fi® + Bluetooth® 5.0, Intel® vPro® technology support, M.2
- Realtek® Wi-Fi® 6 RTL8852AE, 802.11ax Dual Band 2x2 Wi-Fi® + Bluetooth® 5.1, M.2 card^[1]
- Intel® Wi-Fi® 6 AX201, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.1, M.2 Card[2]
- No WLAN and Bluetooth®

Onboard Ethernet

Gigabit Ethernet, Realtek® RTL8111HN, 1x RJ-45, supports Wake-on-LAN

Notes:

[1], [2] Bluetooth® 5.2 is hardware ready but may run at a lower version due to OS limitations.

Ports^[1]

Front Ports

- 1x USB-C® 3.2 Gen 1 (support data transfer and 5V@3A charging)
- 2x USB 3.2 Gen 1
- 1x headphone / microphone combo jack (3.5mm)
- 1x microphone (3.5mm)

Optional Front Ports

1x card reader

Rear Ports^{[2][3]}

- 2x USB 2.0
- 2x USB 3.2 Gen 1 (one supports Smart Power On)
- 1x HDMI® 2.1 TMDS
- 1x DisplayPort[™] 1.4
- 1x VGA
- 1x Ethernet (RJ-45)
- 1x line-out (3.5mm)

Optional Rear Ports**

- 2x USB 2.0 (via 2-port adapter)
- 1x parallel
- 1x serial
- 1x 2nd serial
- None

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the



host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

[2] For video ports on discrete graphics, please see graphics section.

[3] Onboard video ports are only available for the models with integrated graphics.

SECURITY & PRIVACY

Security

Security Chip

Discrete TPM 2.0, TCG certified

Physical Locks

- (Optional) Smart Cable Clip
- Kensington® Security Slot™, 3 x 7 mm
- Padlock Loop

Chassis Intrusion Switch

- · Chassis intrusion switch
- · No chassis intrusion switch

Fingerprint Reader

No fingerprint reader

BIOS Security

- · Hard disk password
- · Power-on password
- · Supervisor password
- Cover presence switch
- Intel® BIOS guard
- Secure wipe
- Smart USB protection (allows keyboard / mouse only, blocks all storage devices)
- More BIOS security features, please visit <u>BIOS Simulator</u>[1]

Notes:

[1] The BIOS simulator is just for reference. Default settings and some options may vary depending on the hardware, operating system and BIOS version.

MANAGEABILITY

System Management

System Management

Non-vPro®

SERVICE

Warranty⁽¹⁾

Base Warranty**

- 1-year courier or carry-in service
- 1-year limited onsite service
- No base warranty

Notes:

[1] The warranty upgrades may be bundled with some models, please check the "Included upgrade" column in the specific model's configurations. For more service extensions, please go to https://smartfind.lenovo.com/. To learn more details of



warranty policy, please access https://support.lenovo.com/warrantylookup/warrantypolicy.

ACCESSORIES

Bundled Accessories

Bundled Accessories

- DP to DVI donale
- DP to Dual DP dongle
- DP to HDMI® dongle
- DP to VGA dongle
- HDMI® to HDMI® dongle
- HDMI® to VGA dongle
- Smart Cable (USB-A to USB-C®)
- None

OPERATING REQUIREMENTS

Operating Environment

Temperature

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage: -40°C (-40°F) to 60°C (140°F)

Relative Humidity

- Operating: 20% to 80%
- Storage: 10% to 90%

Altitude

- Operating: 0 m (0 ft) to 3048 m (10,000 ft)
- Storage: 0 m (0 ft) to 12192 m (40,000 ft)

CERTIFICATIONS

Green Certifications

- (Optional) ENERGY STAR® 8.0
- (Optional) EPEAT™ Silver Registered[2]
- (Optional) EPEAT™ Gold Registered^[3]
- ErP Lot 3
- RoHS compliant
- TCO Certified

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit https://compliance.lenovo.com.

[2], [3] EPEAT™ is registered where applicable, please visit epeat.net for registration status by country.

Other Certifications

Other Certifications

- (Optional) TÜV Rheinland® Low Noise
- (Optional) TÜV Rheinland® Ultra Low Noise
- Feature with ** means that only one option listed under the feature can be configured on selected models.

 Please refer to the model configuration for specific information.
- Feature with *** means that one or more options listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES

ThinkCentre neo 50s



OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.

• The specifications on this page may not be available in all regions, and may be changed or updated without notice





intel.

intel.

intel.



intel





intel





intel