

# **OVERVIEW**





| 1. Smart card reader *           | 5. USB-C 3.2 Gen 2                           |
|----------------------------------|--|
| 2. USB 3.2 Gen 1                 | 6. HDMI                                      |
| 3. Kensington Nano Security Slot | 7. USB 3.2 Gen 1 (Always On)                 |
| 4. USB4                          | 8. Headphone / microphone combo jack (3.5mm) |

# Notes:

- Items with \* are only available on selected models
- Optional nano-SIM card slot on the rear side (not shown on the sample product above)



# **PERFORMANCE**

## **Processor**

### **Processor Family**

AMD Ryzen™ 5 / 7 Processor

### Processor\*\*

| Processor Name         | Cores | Threads | Base Frequency | Max Frequency | Cache            | Processor Graphics |
|------------------------|-------|---------|----------------|---------------|------------------|--------------------|
| AMD Ryzen™ 5 PRO 6650U | 6     | 12      | 2.9GHz         | 4.5GHz        | 3MB L2 / 16MB L3 | AMD Radeon™ 660M   |
| AMD Ryzen™ 7 PRO 6850U | 8     | 16      | 2.7GHz         | 4.7GHz        | 4MB L2 / 16MB L3 | AMD Radeon™ 680M   |

# **Operating System**

# Operating System\*\*

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- Windows® 11 DG Windows® 10 Pro 64
- Windows® 10 IoT Enterprise LTSC 2021[1]
- Ubuntu Linux<sup>[2]</sup>
- Linux<sup>[3]</sup>
- · No preload operating system

#### Notes:

[1] Windows® 10 IoT Enterprise LTSC 2021 is for special bid only.

[2], [3] Some features may not be supported on the system with Linux preload, including but not limited to Intel® RST RAID, MIPI computer vision camera, WWAN, Human Presence Detection, etc.

# **Graphics**

# Graphics\*\*

| Graphics         | Туре       | Memory | Key Features |
|------------------|------------|--------|--------------|
| AMD Radeon™ 660M | Integrated | Shared | DirectX® 12  |
| AMD Radeon™ 680M | Integrated | Shared | DirectX® 12  |

# **Monitor Support**

## **Monitor Support**

Supports up to 4 independent displays (native display and 3 external monitors via HDMI® and USB-C®)

- HDMI® supports up to 4K@60Hz
- USB-C $^{\circ}$  supports up to 4K $^{\circ}$ 60Hz (4 displays output), 5K $^{\circ}$ 60Hz (3 displays output) or 5K $^{\circ}$ 120Hz (up to 2 displays output)

# Chipset

## Chipset

AMD SoC (System on Chip) platform

### Memory

## **Max Memory**

- 8GB soldered memory, not upgradable
- 16GB soldered memory, not upgradable
- 32GB soldered memory, not upgradable

## **Memory Slots**

Memory soldered to systemboard, no slots, dual-channel

## **Memory Type**

LPDDR5-6400

# **Storage**

Storage Support[1]

# ThinkPad T14s Gen 3 (AMD)



One drive, up to 2TB M.2 2280 SSD

#### **Storage Slot**

One M.2 2280 PCIe® 4.0 x4 slot

### Storage Type\*\*

| Disk Type    | Interface                             | Offering            | Security |
|--------------|---------------------------------------|---------------------|----------|
| M.2 2280 SSD | PCIe® NVMe®, PCIe® 4.0 x4             | 256GB / 512GB / 1TB | Opal 2.0 |
| M.2 2280 SSD | PCIe® NVMe®, PCIe® 4.0 x4 Performance | 512GB / 1TB / 2TB   | Opal 2.0 |

#### Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

# Removable Storage

### **Card Reader**

No card reader

## Multi-Media

### **Audio Chip**

High Definition (HD) Audio, Realtek® ALC3287 codec

### **Speakers**

Stereo speakers, 2W x2, Dolby Audio™

### Microphone

- Dual-microphone array, 360° far-field, Dolby Voice®
- · No microphone

#### Camera\*\*

- FHD 1080p + IR hybrid, with privacy shutter, fixed focus
- FHD 1080p, with privacy shutter, fixed focus
- HD 720p, with privacy shutter, fixed focus
- · No camera

# **Battery**

# **Battery**

Integrated Li-Polymer 57Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter

## Battery Life[1]

Configuration 1 (max battery life)

MobileMark® 2018: up to 19.52 hr with 707 performance score @200nits

MobileMark® 25: up to 18.18 hr with 564 performance score @250nits

JEITA 2.0: up to 22.98 hr @150nits

Local video playback: up to 22.1 hr @150nits

## Alternate configuration 2

MobileMark® 2018: up to 14.68 hr with 698 performance score @200nits

MobileMark® 25: up to 13.47 hr with 553 performance score @250nits

JEITA 2.0: up to 20.22 hr @150nits

Local video playback: up to 18.1 hr @150nits

## Alternate configuration 3

MobileMark® 2018: up to 10.68 hr with 806 performance score @200nits

MobileMark® 25: up to 9.78 hr with 539 performance score @250nits

JEITA 2.0: up to 12.75 hr @150nits

Local video playback: up to 10.5 hr @150nits

## Notes:

[1] Configuration 1 (max battery life): WUXGA Low Power (non-touch), AMD Ryzen™ 7 PRO 6850U, 16GB LPDDR5, Win 11, 57Wh battery, best power efficiency power mode

Alternate configuration 2: WUXGA 300nits (touch), AMD Ryzen™ 5 PRO 6650U, 16GB LPDDR5, Win 11, 57Wh battery, best power efficiency power mode

Alternate configuration 3: 2.8K OLED, AMD Ryzen™ 5 PRO 6650U, 32GB LPDDR5, Win 11, 57Wh battery, best power



### efficiency power mode

All battery life claims are approximate maximum and based on results using MobileMark® 2018, MobileMark® 25, JEITA 2.0, continuous 1080p local video playback (using default Media Player in Fullscreen mode with 150nits brightness and default volume level), or Google Power Load Test (PLT) battery-life benchmark tests.

Actual battery life will vary depending on many factors such as product configuration, software, wireless functionality, power management settings, and screen brightness.

The maximum capacity of the battery will decrease with time, ambient temperature and use.

Refer to Microsoft® link for more information about the Windows® Performance power slider.

# **Power Adapter**

# Power Adapter\*\*[1]

- 45W USB-C<sup>®</sup> (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 45W USB-C® (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- No power adapter<sup>[2]</sup>

#### Notes:

- [1] AC adapter offerings depend on the country.
- [2] No power adapter is for special bid only.

# DESIGN

# **Display**

## Display\*\*

| Size | Resolution           | Touch           | Туре               | Brightness | Surface  | Aspect<br>Ratio | Contrast<br>Ratio | Color<br>Gamut | Viewing<br>Angle<br>(L/R/U/D) | Key Features   |
|------|----------------------|-----------------|--------------------|------------|--|-----------------|-------------------|----------------|-------------------------------|--|
| 14"  | WUXGA<br>(1920x1200) | Multi-<br>touch | IPS <sup>[1]</sup> | 300nits    | Anti-glare   | 16:10           | 600:1             | 45%<br>NTSC    | 85° / 85° /<br>85° / 85°      | -  |
| 14"  | WUXGA<br>(1920x1200) | None            | IPS <sup>[2]</sup> | 300nits    | Anti-glare   | 16:10           | 600:1             | 45%<br>NTSC    | 85° / 85° /<br>85° / 85°      | -  |
| 14"  | WUXGA<br>(1920x1200) | None            | IPS <sup>[3]</sup> | 400nits    | Anti-glare   | 16:10           | 800:1             | 100%<br>sRGB   | 85° / 85° /<br>85° / 85°      | Low power,<br>Eyesafe® Certified                                       |
| 14"  | WUXGA<br>(1920x1200) | Multi-<br>touch | IPS <sup>[4]</sup> | 500nits    | Anti-glare   | 16:10           | 800:1             | 100%<br>sRGB   | 85° / 85° /<br>85° / 85°      | ThinkPad® Privacy<br>Guard   |
| 14"  | 2.2K<br>(2240x1400)  | None            | IPS <sup>[5]</sup> | 300nits    | Anti-glare   | 16:10           | 1000:1            | 100%<br>sRGB   | 85° / 85° /<br>85° / 85°      | TÜV Low Blue<br>Light (Hardware<br>Solution)                           |
| 14"  | 2.8K<br>(2880x1800)  | None            | OLED               | 400nits    | Anti-glare,<br>anti-<br>reflection,<br>anti-smudge | 16:10           | 100,000:1         | 100%<br>DCI-P3 | 85° / 85° /<br>85° / 85°      | DisplayHDR™ True<br>Black 500, Dolby<br>Vision®, Eyesafe®<br>Certified |

# **Touchscreen**

- On-cell multi-touch, supports 10-point touch
- Non-touch

## Notes:

[1], [2], [3], [4], [5] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

# **Input Device**

### Keyboard

6-row, spill-resistant, multimedia Fn keys with Unified Communications controls



### **Keyboard Backlight**

- · LED backlight
- · Non-backlight

### UltraNav™

TrackPoint® pointing device and glass-like Mylar® surface multi-touch touchpad, 61 x 115 mm (2.40 x 4.53 inches)

### Mechanical

### Dimensions (WxDxH)[1]

317.5 x 226.9 x 16.9 mm (12.5 x 8.93 x 0.67 inches)

### Weight<sup>[2]</sup>

Starting at 1.23 kg (2.71 lbs)

### Case Color\*\*

- · Storm grey
- Thunder black

#### Case Material\*\*

- Storm grey models: aluminium (top), aluminium (bottom)
- Thunder black models: carbon fiber hybrid (top), aluminium (bottom)

#### Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

# CONNECTIVITY

# Network

# Ethernet

No onboard Ethernet[1]

# WLAN + Bluetooth®\*\*[2]

- MediaTek Wi-Fi® 6E RZ616, 802,11ax 2x2 Wi-Fi® + Bluetooth® 5.1 (Bluetooth® 5.2 hardware ready)[3]
- Qualcomm® Wi-Fi® 6E NFA725A, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.1 (Bluetooth® 5.2 hardware ready)[4]

### WWAN\*\*

- Wireless WAN upgradable to 4G (with antenna ready)
- · Quectel EM05-G, 4G LTE CAT4, M.2 card
- Fibocom L860-GL-16, 4G LTE CAT16, M.2 card
- Fibocom FM350-GL, 5G Sub-6 GHz, M.2 Card, with embedded eSIM functionality
- · No support

### SIM Card

- Gemalto eSIM card (physical)
- No physical SIM card inbox

### NFC

- · Near Field Communication
- No support

### Notes:

[1] Ethernet support via optional Lenovo® USB-C® to Ethernet Adapter.

[2] Bluetooth® may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.

[3], [4] Wi-Fi® 6E full features might be limited by country-level restrictions.

Wi-Fi® 6E is only enabled on Windows® 11 and operates as Wi-Fi® 6 with Windows® 10.

6GHz Wi-Fi® 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi® 6E, and the regional regulatory certifications & spectrum allocation.

## **Ports**<sup>[1]</sup>



#### **Standard Ports**

- 1x USB 3.2 Gen 1
- 1x USB 3.2 Gen 1 (Always On)
- 1x USB-C® 3.2 Gen 2 (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.4a)
- 1x USB4® 40Gbps (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.4a)
- 1x HDMI® 2.1, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)

### Optional Ports\*\*\*

- 1x Smart card reader
- 1x Nano-SIM card slot (WWAN support models)

#### Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

# **Docking**

### **Docking**

Various docking solutions supported via USB-C<sup>®</sup>.

For more compatible docking solutions, please visit Docking for ThinkPad® T14s Gen 3 (AMD)

# **SECURITY & PRIVACY**

# **Security**

### **Security Chip**

Discrete TPM 2.0 (TCG certified, FIPS 140-2 certified) and Microsoft® Pluton TPM 2.0, one enabled at one time

### **Physical Locks**

Kensington® Nano Security Slot™, 2.5 x 6 mm

# **Smart Card Reader**

- Smart card reader, supports ISO 7816 and EMV
- No smart card reader

## **Fingerprint Reader**

- Touch style fingerprint reader integrated in power button, match-on-chip
- No fingerprint reader

## **BIOS Security**

- · Supervisor password
- Power-on password
- · System management password
- NVMe® password
- Certificate based BIOS authentication
- FIDO (Fast Identity Online) authentication
- · Self-healing BIOS

### **Other Security**

- Camera privacy shutter (camera models)
- (Optional) IR camera for Windows® Hello (facial recognition)
- Glance by Mirametrix®
- (Optional) Human Presence Detection

# **MANAGEABILITY**

# **System Management**



### **System Management**

- DASH
- Non-DASH

# **SERVICE**

# Warranty

### Base Warranty\*\*

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 1-year limited onsite service
- 3-year (1-yr battery) courier or carry-in service
- · 3-year (1-yr battery) limited onsite service
- No base warranty

# **ACCESSORIES**

# **Bundled Accessories**

### **Bundled Accessories**\*\*\*[1]

- Lenovo® HDMI® to VGA Monitor Adapter
- Lenovo® USB-C® to DisplayPort™ Adapter
- Lenovo® USB-C® to Ethernet Adapter (1Gbps)
- Lenovo® USB-C® to VGA Adapter
- None

Notes:

[1] For more compatible accessory solutions, please visit Accessories for ThinkPad® T14s Gen 3 (AMD).

# OPERATING REQUIREMENTS

# **Operating Environment**

## Temperature[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

# **Relative Humidity**

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

### Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than  $10^{\circ}\text{C}$  (50°F).

# ENVIRONMENTAL

## Sustainability

# Material

97% PCC recycled plastic used in speaker enclosure

97% recycled plastic used in the 57Wh battery frame

95% PCC recycled plastic used in standard 65W adapter

Low-temperature solder

90% recycled and/or sustainable packaging

# **CERTIFICATIONS**



## Green Certifications<sup>11</sup>

### Green Certifications[2]

- ENERGY STAR® 8.0
- EPEAT™ Gold Registered[3]
- ErP Lot 3
- RoHS compliant
- TCO Certified 9.0

#### Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <a href="https://compliance.lenovo.com">https://compliance.lenovo.com</a>.

[2] EPEAT™ registration and ENERGY STAR® certification are dependent on system OS. Please visit <u>epeat.net</u> and <u>energystar.gov</u> for more information.

[3] EPEAT™ is registered where applicable, please visit epeat.net for registration status by country.

## **Other Certifications**

# Mil-Spec Test

MIL-STD-810H military test passed

#### Other Certifications

- (Optional) Eyesafe® Certified
- (Optional) TÜV Rheinland® Low Blue Light (Hardware Solution)
- Feature with \*\* means that only one offering listed under the feature is configured on selected models.
- Feature with \*\*\* means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without
  notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES
  THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING
  THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some
  jurisdictions do not allow disclaimer of express or implied warranties in certain
  transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.







AMD









AMDA