

OVERVIEW



1. Power connector	8. USB-B 3.2 Gen 1
2. Kensington Security Slot	9. HDMI 2.1 TMDS
3. USB 3.2 Gen 1	10. HDMI 2.1 TMDS
4. USB 3.2 Gen 1	11. DisplayPort 1.2
5. Ethernet (RJ-45)	12. Audio-out (3.5mm)
6. Thunderbolt 4 Out	13. USB-C 3.2 Gen 1
7. Thunderbolt 4 In	14. USB 3.2 Gen 1

PERFORMANCE

Panel

Panel
3-side NearEdgeless, In-Plane Switching

Backlight
WLED

Display Size
27 inches

Max View Area

- Active Area: 596.7 x 335.7 mm
- Screen Dimension: 608.8 x 352.3 mm

Resolution
3840 x 2160

Aspect Ratio
16:9

Pixel Pitch
0.1554 x 0.1554 mm

Dot / Pixel Per Inch
163 dpi

Brightness

- Peak: 450 cd/m²
- Typical: 400 cd/m²

Contrast Ratio

- Contrast Ratio: 1000:1
- Dynamic Contrast Ratio (Typical): 3000000:1

View Angle (H / V)
Horizontal: 178°, Vertical: 178°

Response Time

- Extreme Mode: 4 ms
- Normal Mode: 6 ms

Refresh Rate
60Hz

Color Gamut

- 100% sRGB (CIE 1976)
- 99.1% DCI-P3 (CIE 1976)
- 100% BT.709 (CIE 1976)
- 83.7% BT.2020 (CIE 1976)
- 99.5% Adobe® RGB (CIE 1931)

Color Support
1.07 Billion

Color Depth
10-bit (8-bit+FRC)

Screen Surface Treatment
Anti-glare

Operating System

Operating System

- Windows® 11 Support
- Windows® 10 Support
- Windows® 7 Support

Multi-Media

Camera

- ThinkVision® MC 50 monitor webcam (Some models only)
- No bundled webcam (Support ThinkVision® MC 50 Monitor Webcam, sold separately)

Speakers

- Integrated Speakers, 3W x2
- Optional Soundbar support (PN: OA36190)

Power Supply

Power Consumption

- Typical / Max: 35W / 240W
- Sleep / Off mode: <0.5W
- Switch-off Mode: <0.3W
- Energy Star Power On: 26W
- Energy Star TEC: 97kWh
- Internal Power Supply

Voltage Required

AC 100 to 240 V (50-60Hz)

Special Features

Special Features

- DisplayHDR™ 400
- Factory Calibration: Avg. Delta E<1
- Lenovo® ThinkColour (Lenovo® Accessories and Display Manager) Support
Lenovo® ThinkColour supports Windows® 10 & 11, Mac OS, and Windows® On Arm (functions vary across systems).
Lenovo® Accessories and Display Manager is formerly Lenovo® Display Control Center.
- KVM Switch
- Shading Hood Support (To be ordered optionally with the monitor)
- Smart Light
- Smart Power
The Smart Power function intelligently detects overall power consumption and dynamically manages the power delivery to each device

DESIGN

Mechanical

ThinkCentre® M Series Support

ThinkCentre® M Series Tiny, ThinkCentre® M Series Nano
For supporting Tiny devices, additional Tiny monitor clamp II (PN: 4XH0Z42451) and Tiny VESA mount II (PN: 4XF0N03161) are needed (sold separately).
For supporting Nano devices, additional Nano monitor clamp II (PN: 4XH0Z42451) and Nano VESA mount (PN: 4XF0V81630) are needed (sold separately).

Bezel Width

- Side: 2.0mm
- Top / Bottom: 2mm / 23.6mm

Cable Management

Support

Case Color

Raven black

Dimensions (WxDxH)^[1]

Models	Dimensions
Lowest Position	613.8 x 219.9 x 421.4 mm (24.16 x 8.66 x 16.59 inches)
Highest Position	613.8 x 219.9 x 556.4mm (24.16 x 8.66 x 21.90 inches)
Head Only	613.8 x 52.9 x 368.8 mm (24.16 x 2.08 x 14.52 inches)

Packaging Dimensions (WxDxH)

732 x 187 x 510 mm (28.82 x 7.36 x 20.08 inches)

Weight^[2]

Models	Weight
Monitor With Stand	8.0 kg (17.6 lbs)
Monitor Head Only	5.4 kg (11.9 lbs)

Packaging Weight

12.8 kg (28.22 lbs)

Mounting

Supports VESA mount 100mm

Stand

Supports -5° to +35° tilt, left & right 45° swivel, -90° to 90° pivot, up to 135mm lift

In the Box

- Monitor with stand
- 1x DP cable (1.8m) (for US, Canada only)
- 1x USB-C® to USB-A cable (1.8m)
- 1x Power cable (1.8m)
- 1x Thunderbolt™ 4 cable (40Gbps)
- Factory calibration report
- Quick setup guide

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Ports^[1]

Rear Ports^[2]

- 1x Thunderbolt™ 4 In
- 1x Thunderbolt™ 4 Out
- 1x USB-C® 3.2 Gen 1 (data transfer, up to 27W), USB downstream
- 1x USB-B 3.2 Gen 1, USB upstream
- 3x USB 3.2 Gen 1 (1x BC 1.2), USB downstream
- 2x HDMI® 2.1 TMDS^[3]
- 1x DisplayPort™ 1.2
- 1x Ethernet (RJ-45)
- 1x Power Connector
- 1x audio-out (3.5mm)

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

Thunderbolt™ 5: 80 Gbit/s (bidirectional), up to 120 Gbit/s in bandwidth boost mode for video-intensive applications.

[2] Up to 27W power delivery to compatible devices by USB-C®. Listed as maximum capacity of power delivery. Actual capacity of power delivery may vary depending upon devices connected or monitor configuration, and may decline with downstream USB ports connected or higher brightness setting.

[3] Supports 3840x2160@60Hz as specified in HDMI® 2.1.

SECURITY & PRIVACY

Security

Physical Locks

Kensington® Security Slot™

SERVICE

Warranty

Base Warranty

3-year limited warranty

OPERATING REQUIREMENTS

Operating Environment

Temperature

Operating: 0°C to 40°C (32°F to 104°F)

Storage: -20°C to 60°C (-4°F to 140°F)

Relative Humidity

Operating: 8% to 80%

Storage: 5% to 95%

CERTIFICATIONS

Green Certifications^[1]

Green Certifications

- ENERGY STAR® Certified
- EPEAT™ Gold Registered^[2]
- RoHS compliant
- TCO Certified 9.0
- TCO edge 2.0

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <https://compliance.lenovo.com>.

[2] EPEAT™ is registered where applicable, please visit epeat.net for registration status by country.

Other Certifications

Other Certifications

TÜV Rheinland® Eye Comfort Certification

- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. **LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

