

OVERVIEW



1. Power connector	8. Ethernet (RJ-45)
2. HDMI 2.1 TMDS	9. USB 3.2 Gen 2
3. HDMI 2.1 TMDS	10. USB 3.2 Gen 2
4. DisplayPort 1.4	11. Audio-out (3.5mm)
5. DisplayPort 1.4 out	12. USB-C 3.2 Gen 2
6. USB4 40Gbps	13. USB 3.2 Gen 2
7. USB-C 3.2 Gen 2	14. USB 3.2 Gen 2

PERFORMANCE

Panel

Panel
3-side NearEdgeless, In-Plane Switching

Backlight

Mini-LED

Display Size

31.5 inches

Max View Area

- Active Area: 697.3 x 392.2 mm
- Screen Dimension: 709.6 x 417.8 mm

Resolution

3840 x 2160

Aspect Ratio

16:9

Pixel Pitch

0.182 x 0.182 mm

Dot / Pixel Per Inch

140 dpi

Brightness

- Peak: 1200 cd/m²
- Typical: 650 cd/m²

Contrast Ratio

- Contrast Ratio: 1000:1
- Dynamic Contrast Ratio (Typical): 3000000:1

View Angle (H / V)

Horizontal: 178°, Vertical: 178°

Response Time

- Extreme Mode: 4 ms
- Normal Mode: 6 ms

Refresh Rate

60Hz

Color Gamut

- 100% sRGB
- 98% DCI-P3
- 100% BT.709
- 81% BT.2020
- 99% Adobe® RGB

Color Support

1.07 Billion

Color Depth

10-bit (8-bit+FRC)

Screen Surface Treatment

Anti-glare

Curvature

Flat Panel

Operating System

Operating System

- Windows® 11 Support
- Windows® 10 Support

Multi-Media

Camera

Optional Modular Camera Support

Speakers

Optional Modular Soundbar support

Power Supply

Power Consumption

- Typical / Max: 32W / 305W
- Sleep / Off mode: <0.5W / <0.3W
- Switch-off Mode: <0.3W
- Energy Star Power On: 32.3W
- Energy Star TEC: 101.9kWh
- Internal Power Supply

Voltage Required

AC 100 to 240 V (50-60Hz)

Special Features

Special Features

- HDR10 Compliance
- DisplayHDR™ 1000
- Factory Calibration: Avg. Delta E<1.5
- Picture In Picture (PIP) / Picture By Picture (PBP) Support
- Lenovo® ThinkColour (Lenovo® Accessories and Display Manager) Support
Lenovo® ThinkColour supports Windows® 10 & 11, Mac OS, and Windows® On Arm (functions vary across systems).
Lenovo® Accessories and Display Manager is formerly Lenovo® Display Control Center.
- HLG
- KVM Switch
- Smart Power
The Smart Power function intelligently detects overall power consumption and dynamically manages the power delivery to each device
- Smart Sensor (Ambient Light Sensor, Human Detection Sensor)

DESIGN

Mechanical

ThinkCentre® M Series Support

ThinkCentre® M Series Tiny, ThinkCentre® M Series Nano
For supporting Tiny / Nano devices, additional Clamp Bracket Mounting Kit III (PN: 4XF1K72399) is needed (sold separately).

Bezel Width

- Side: 2.0mm
- Top / Bottom: 2mm / 29mm

Case Color

Raven black

Dimensions (WxDxH)^[1]

Models	Dimensions
Lowest Position	714.2 x 234.9 x 456.6 mm (28.12 x 9.25 x 17.98 inches)
Highest Position	714.2 x 234.9 x 609 mm (28.12 x 9.25 x 23.98 inches)
Head Only	714.2 x 78.9 x 430.9 mm (28.12 x 3.11 x 16.96 inches)

Packaging Dimensions (WxDxH)

908 x 163 x 518 mm (35.75 x 6.42 x 20.39 inches)

Weight^[2]

Models	Weight
--------	--------

Monitor With Stand	10.5 kg (23.1 lbs)
Monitor Head Only	7.6 kg (16.8 lbs)

Packaging Weight

14.6 kg (32.2 lbs)

Mounting

Supports VESA mount 100 x 100 mm

Stand

Supports -5° to +23.5° tilt, left & right 45° swivel, 90° pivot, up to 155mm lift

In the Box

- Monitor with stand
- 1x DP cable (1.8m) (for US, Canada only)
- 1x USB-C® to USB-A gen 2 cable (1m)
- 1x USB4® cable (1m)
- 1x Power cable (1.8m)
- Factory calibration report
- Quick setup guide

Notes:

- [1] The system dimensions may vary depending on configurations.
- [2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet

Support 10M / 100M / 1000M

Ports^[1]

Rear Ports

- 1x USB-C® 3.2 Gen 2 (support data transfer, up to 15W PD), USB downstream
- 1x USB-C® 3.2 Gen 2, USB upstream
- 1x USB4® 40Gbps (support data transfer, DP 1.4 Alt Mode and up to 140W PD), USB upstream
- 4x USB 3.2 Gen 2 (1x BC 1.2), USB downstream
- 2x HDMI® 2.1 TMDS, supports 3840x2160@60Hz
- 1x DisplayPort™ 1.4
- 1x DisplayPort™ 1.4 (Out)
- 1x Ethernet (RJ-45)
- 1x audio-out (3.5mm)

Notes:

- [1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.
- USB 2.0: 480 Mbit/s;
- USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
- USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
- USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
- USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;
- Thunderbolt™ 3/4: 40 Gbit/s.
- Thunderbolt™ 5: 80 Gbit/s (bidirectional), up to 120 Gbit/s in bandwidth boost mode for video-intensive applications.

SECURITY & PRIVACY

Security

Physical Locks

Kensington® Security Slot™ (2.5 mm x 6 mm and 3 mm x 7 mm)

SERVICE

Warranty

Base Warranty

3-year limited warranty

OPERATING REQUIREMENTS

Operating Environment

Temperature

Operating: 0°C to 40°C (32°F to 104°F)

Storage: -20°C to 60°C (-4°F to 140°F)

Transport: -20°C to 60°C (-4°F to 140°F)

Relative Humidity

Operating: 8% to 80% non-condensing

Storage: 5% to 95% non-condensing

Transport: 5% to 95% non-condensing

CERTIFICATIONS

Green Certifications^[1]

Green Certifications

- ENERGY STAR® Certified
- EPEAT™ Gold Registered
- EU Energy Label (G-class)
- RoHS compliant
- Volatile Organic Compound Certification

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <https://compliance.lenovo.com>.

Other Certifications

Other Certifications

- TÜV Rheinland® Eye Comfort Certification
 - TÜV Rheinland® Flicker Free
 - TÜV Rheinland® Low Blue Light
-
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
 - The specifications on this page may not be available in all regions, and may be changed or updated without notice.

